



NATURE PROTECT® BIOSOURCED ULTRA PROTECT OIL

Nourishes, protects and beautifies wooden garden furniture. Nature Protect® Ultra Protect Biosourced* Oil contains 90% natural*, mineral and biosourced ingredients. The quality of the formulations in the Nature Protect® range is recognised by AFPRAL, which recommends this product to reduce the risk of respiratory allergies.

* Tested according to the NF EN 16640 standard and not derived from organic farming

• Directly onto new wood, without prior ageing

- Garden furniture
- Designed for outdoor use

1

STEP

PREPARATION

- **New exotic woods:** remove grease with a cloth soaked in acetone.
- **Old, stained or grey untreated wood:** clean with the **Syntilor Dégriseur Bois**.
- **Old finishes (paint, varnish, etc.):** sand with 40, 60 then 100 grain sandpaper or strip first with a **Syntilor Stripper**.
- If necessary, treat with a suitable wood treatment product.

ADVICE FROM THE PROFESSIONAL

After preparation, sand all surfaces with 100 grain sandpaper to open the pores of the wood and facilitate penetration of the product.

2

STEP

APPLICATION

- Ready-to-use product, do not dilute.
- Shake well before and during use.
- Apply a thin first coat following the direction of the grain (making sure the grooves, joints and ends are well coated).
- Leave to penetrate for 30 minutes.
- Use a brush to smooth any excess product away and avoid runs and sags.
- Wait at least 12 hours before putting back into use.

3

STEP

MAINTENANCE

- As soon as the wood surface naturally lightens as a result of bad weather and UV light, apply **Nature Protect Biosourced Ultra Protect Oil** directly to faded areas.
- In the event of delayed maintenance, clean first with the **Syntilor Dégriseur Bois**.




TECHNICAL CHARACTERISTICS

Density (at 20°C)	About 1.02
CONSISTENCY	Fluid liquid
DRYING TIME (at 20°C)	Between coats: 30 minutes Fully dry: 12 hrs
COVERAGE	20 m ² per litre per coat
FINISH	Matt

PRECAUTIONS & STORAGE

- Do not tint or stain beforehand. Do not apply over any other oil.
- First, make sure that the wood is dry: at least 3 days of good weather before application and without risk of rain within the 24 hours after application of the second coat.
- Use outdoors or in a well-ventilated area only.
- Do not apply at a temperature below 12° C or above 25° C.
- Keep out of reach of children.
- Store in the original packaging, carefully closed after use.
- Store away from frost, heat and humidity.
- The Safety Data Sheet for this product is available on our website www.syntilor.com

TOOLS



TOOL CLEANING



TOOLS & CLEANING